

Amendments to the Claims:

The following listing of claims will replace all prior versions, and listings, of claims in the application:

1. (Previously Presented) Method for using utilizable data, in data formats which cannot be directly processed, in communication, in particular wireless communication, between at least two geodetic devices comprising
 - a first device having communication means,
 - a second device having
 - communication means,
 - means for processing utilizable data and
 - storage means,
 - comprising the steps
 - transmission of data by the first device, the data being transmitted in data formats having a sequence of at least two data fields,
 - reception of the data and processing of utilizable data by the second device, the utilizable data being read from data fields which can be evaluated,
 - characterized in that particularly in relation to the transmission of the data, at least one reference directory is transmitted and is stored in the storage means, the reference directory indicating, in data formats which cannot be directly processed, the data fields which can be evaluated, and wherein the means for processing utilizable data employ the reference directory stored in the storage means for evaluating data received by the communication means,
 - characterized in that the utilizable data is transmitted in its original format, and

characterized in that the reference directory is transmitted separately from the utilizable data.

2. (Original) Method according to Claim 1, characterized in that a data directory in which data fields and/or data types are defined is transmitted.

3. (Previously Presented) Method according to Claim 1, characterized in that the data formats are uniquely defined by a coding, in particular a numeric or alphanumeric coding.

4. (Previously Presented) Method according to Claim 1, characterized in that, in one of the data formats, at least one data field with a fixed length is chosen, in particular with a length required by the format of geodetic location or time data.

5. (Previously Presented) Method according to Claim 1, characterized in that, when receiving the data or processing utilizable data, at least one data field which cannot be evaluated is suppressed in the data format which cannot be directly processed, so that only one sequence of data fields which can be evaluated is received and/or evaluated.

6. (Previously Presented) Method according to Claim 1, characterized in that, when receiving the data or processing utilizable data in data formats which cannot be directly processed, at least one data field which can be evaluated is localized within the sequence of data fields.

7. (Previously Presented) Method according to Claim 1, characterized in that the indication of data fields which can be evaluated in the reference directory is effected by at least one of the two measures

specification of the sequence of data fields in data formats which cannot be directly processed, so that data fields which can be evaluated are localized,

specification of a change of known data formats, so that the sequence of data fields in the data formats which cannot be directly processed can be derived and data fields which can be evaluated can be localized.

8. (Previously Presented) Method according to Claim 1, characterized in that, on transmission of the data, the first device transmits data to a plurality of second devices.

9. (Previously Presented) Method according to Claim 1, characterized in that the transmission of the reference directory is initiated by at least one of the following measures

establishment of a communication connection between first and second device,
detection of a set time mark, in particular periodic time mark, during the
existence of a communication connection between first device and second device,

elapse of a counting procedure,

execution of a defined procedure in the first device,

transmission of a message by the second device indicating that a data format
which cannot be directly processed is being received or was received,

transmission of a message by the second device, in which message the data
formats which can be directly processed by this second device are defined.

10-11. (Canceled)

12. (Previously Presented) Reference directory or data directory as a code which
is stored on a machine-readable medium, for carrying out the method according to Claim 1, in
particular if the code is used in a computer.

13. (Canceled)

14. (Previously Presented) Geodetic device, in particular reference station for
differential GNSS or theodolite, as a first device for carrying out the method according to
Claim 1, comprising communication means, characterized in that the communication means
are designed for transmitting a reference directory or data directory.

15. (Previously Presented) Geodetic device according to Claim 14, characterized in that the communication means are formed so that the transmission of the reference directory or of the data directory is initiated by at least one of the following events

establishment of a communication connection to a second device,

detection of a set time mark, in particular of a periodic time mark,

end of a counting procedure,

execution of a defined procedure,

reception of a warning message of a second device stating that a data format which cannot be directly processed is being received or was received,

reception of a message of a second device, in which message the data formats which can be directly processed by this second device are defined.

16. (Previously Presented) Geodetic device, in particular rover for differential GNSS, as a second device for carrying out the method according to Claim 1, comprising

communication means,

means for processing utilizable data and

storage means,

characterized in that the communication means and the storage means are formed and arranged in such a way that a reference directory or a data directory is received and stored.

17. (Previously Presented) Geodetic device according to Claim 16, characterized in that the communication means or the means for processing utilizable data are designed so that data fields which can be evaluated and are contained in data formats which cannot be directly processed are identified by indication in the reference directory.

18. (Previously Presented) Geodetic device according to Claim 16, characterized in that the communication means or the means for processing utilizable data are designed so

that data fields which cannot be evaluated in the data format which cannot be directly processed are suppressed during the reception of the data or the processing of utilizable data.

19. (Previously Presented) Geodetic device according to Claim 16, characterized in that the communication means or the means for processing utilizable data are designed so that data fields which can be evaluated in the data format which cannot be directly processed are localized during the reception of the data or processing of utilizable data within the sequence of data fields.

20. (Canceled)

21. (Previously Presented) A geodetic system, comprising:
at least one of a first geodetic device, in particular reference station for differential GNSS or theodolite, the first geodetic device including a first communication means, wherein the first communication means is designed for separately transmitting (1) a reference directory indicating, in data formats which cannot be directly processed, data fields which can be evaluated and (2) the utilizable data in its original format; and

at least one of a second geodetic device, in particular a rover for differential GNSS, the second geodetic device including a second communication means, means for processing utilizable data and storage means, wherein the second communication means and the storage means are arranged so that the transmitted reference directory is received and stored,

wherein the means for processing utilizable data employ the reference directory stored in the storage means for evaluating data received by the second communication means.